

*Compact & Cost-effective Impact Receipt Printer  
offering easy-to-use solution to the retail and hospitality industries*



Tax control >>



Restaurants >>



Retail >>

# TP200

Compact & Cost-effective Impact Receipt Printer



## Highlights:

- Fast printing speed of up to 4.6 lines per second
- Various interface selections with Serial, Parallel, USB 2.0, Ethernet, Bluetooth, WiFi
- Optimum efficiency with 3-pay forms printout (Original + 2 Copies)

# TP200 Compact & Cost-effective Impact Receipt Printer



**Jolimark TP200**

## User-friendly Design



Media/Ribbon Installation



Media Usage Monitoring Window

Item	Description
Printing method	9 Pins Dot matrix impact
Printing direction	Bidirectional logic seeking
Diameter of wire	0.3 mm
Dot density	160×144DPI (maximum)
Print speed	4.6 lines per second (paper width 76 mm, 40 columns)
Copy	Original + 2 copies
Effective printing width	63 mm (paper width 76 mm), 45 mm (paper width 57 mm)
Paper feed speed	Max:135 mm/s
Line spacing	et by the increment of 1/6 inch or 1/144 inch
Control panel	Touch keys operation, 2 keys and 3 LED indicators
Paper Specification	Roll paper model
	Common single-sheet roll paper Common two-sheet, trilogy roll copy paper
	Width: 57.5 ±0.5 mm, 76 ±0.5 mm Weight: 52.3 ~ 64.0 g/m2 Maximum diameter: Φ83 mm Paper thickness: 0.06 ~ 0.20 mm
	<b>Note: The inner diameter of paper shaft is Φ12 mm and the outer diameter of paper shaft is Φ18 mm.</b>
Character set	ASCII character set, International character set
Ribbon	Type: JMR112 Life: 3 million characters

Interface	Description
This printer can be equipped with the following interfaces	
Parallel interface: Centronics	
USB interface: 2.0 Full-Speed	
USB interface (2.0 Full-Speed) + Serial interface (RS-232C, DB9)	
USB interface (2.0 Full-Speed) + Ethernet interface (10/100Base-T)	
USB interface (2.0 Full-Speed) + Serial interface (RS-232C, DB9) + Ethernet interface (10/100Base-T)	
Bluetooth interface	
Wi-Fi (802.11b/g/n) interface	
Serial+Ethernet+USB interface	



**Note: 1. Only one of the data interfaces is supplied when leaving the factory.  
2. Please take the specific interface as standard.**

Item	Description
Cash drawer interface	RJ-11, 24V(DC)/1A
Black mark	Optional
Special function	Touch keys, Online parameter settings, Software online upgrade
Input buffer	6 KB
Control command	ESC/POS Emulation
	Character printing command: Support ANK characters, user-defined characters and enlarged printing of Chinese characters 1-2 times, can adjust character line spacing
Power Supply (AC adapter)	Input
	Output
Power input	Parameters
	<b>Warning: Please use the original AC adapter only. Manufacturers have no responsibilities for the problems which are led by using unauthorized AC adapter.</b>
Environmental conditions	Operating environment
	Storage environment
Weight	Approx.1.2 Kg
Noise	<58 dB (A) (SO7779 standard)
Physical dimensions	154 (width) × 210 (depth) × 132 mm (height)
Resolution	Horizontal
	Vertical: 144 DPI
Power consumption	1. Operating: 40 W; 2. Standby: Approximately 1.5 W
	<b>Note: Only when the product is unconnected with outer power supply, can it achieve zero energy consumption.</b>

## Certificate



\*The specifications above are subject to be changed without notice.