The New Era for Printing



- Monochrome laser
- Up to 1200*600 dpi
- A high monthly duty cycle of 20,000 pages

- Up to 21 ppm
- 150 pages cassette
- 8MB memory
- USB 2.0 Full-speed



Eco-friendly, protecting the environment

Low carbon footprint Less waste toner residue Low ozone emissions



Cost effective, affordable operation

High quality long life performance High yield cartridge with very low operating costs Lowest Total Cost of Ownership in its class



Metal instead of plastic frame

Solid steel roller bar instead of plastic bar and hard rubber rollers Longer engine life



Built to last and work efficiently

Reliable design lasts for up to 100,000 pages Strong construction with few paper jams Long life high yield consumable options





Print	
Technology	Electrophotographic laser monochrome
Print speed	20 ppm (A4) / 21 ppm (Letter)
First printout time	Less than 10 seconds
Maximum monthly volume	20,000 Pages
Resolution (dpi)	Max. 1200×600dpi
Printer language	GDI
Duplex mode	Manual
Paper	
Automatic paper tray	
Mediatype	Plain, Preprinted, Recycled
Media size	Letter, A4, A5, A6, JISB5, ISOB5, B6, Executive, Statement Oficio, Legal, Big 16k, 32k, 16k, Big 32k, Custom 105mm × 148mm to 216mm × 356mm (4.1"×5.8" to 8.6"×14.2")
Media weight	60-105g/m² (16lb~28lb bond)
Paperinput	150 pages (standard paper 80g/m²(20lb bond))
Paper output	100 pages (standard paper 80g/m²(20lb bond))
Manual feed slot	
Mediatype	Plain, Preprinted, Recycled, Transparency, Card stock, Lab Envelope, Kraft paper
Media size	75mm×148mm to 216mm×356mm(3"×5.8" to 8.6"×14.2
Media weight	60-163g/m² (16lb~43lb bond)
Paper input	1 Page
General	
General Dimensions (WXDXH)	380 mm × 261 mm × 236 mm (15"×10.3"×9.3")
Dimensions (WXDXH)	380 mm × 261 mm × 236 mm (15"×10.3"×9.3") No
Dimensions (W×D×H) Display screen	No
Dimensions (W×D×H) Display screen Weight (with cartridge)	No 6,1 kg(13.4lbs)
Dimensions (W×D×H) Display screen	No
Dimensions (W×D×H) Display screen Weight (with cartridge) Weight (w/o cartridge)	No 6,1 kg(13.4lbs) 5,3 kg(11.7lbs) Recommended temperature: 10-32°C (50-90°F)
Dimensions (W X D X H) Display screen Weight (with cartridge) Weight (w/o cartridge) Recommended environment	No 6,1 kg(13.4lbs) 5,3 kg(11.7lbs) Recommended temperature: 10-32°C (50-90°F) Recommended humidity: 20% - 80% Model depends on the country of purchase: 110-Volt Model: 100-127VAC,50/60Hz, 6.0A
Dimensions (W×D×H) Display screen Weight (with cartridge) Weight (w/o cartridge) Recommended environment Power	No 6,1 kg(13.4lbs) 5,3 kg(11.7lbs) Recommended temperature: 10-32°C (50-90°F) Recommended humidity: 20% - 80% Model depends on the country of purchase: 110-Volt Model: 100-127VAC,50/60Hz, 6.0A 220-Volt Model: 220-240VAC, 50/60Hz, 3.0A
Dimensions (W×D×H) Display screen Weight (with cartridge) Weight (w/o cartridge) Recommended environment Power Noise	No 6,1 kg(13.4lbs) 5,3 kg(11.7lbs) Recommended temperature: 10-32°C (50-90°F) Recommended humidity: 20% - 80% Model depends on the country of purchase: 110-Volt Model: 100-127VAC,50/60Hz, 6.0A 220-Volt Model: 220-240VAC, 50/60Hz, 3.0A Printing: 54dB; Standby: 35dB Printing: Average 350W; Sleep Mode: Less than 6 W
Dimensions (W×D×H) Display screen Weight (with cartridge) Weight (w/o cartridge) Recommended environment Power Noise Power consumption	No 6,1 kg(13.4lbs) 5,3 kg(11.7lbs) Recommended temperature: 10-32°C (50-90°F) Recommended humidity: 20% - 80% Model depends on the country of purchase: 110-Volt Model: 100-127VAC,50/60Hz, 6.0A 220-Volt Model: 220-240VAC, 50/60Hz, 3.0A Printing: 54dB; Standby: 35dB Printing: Average 350W; Sleep Mode: Less than 6 W Microsoft Windows Server2003 / Server2008 / Server2012 XP / Vista / Windows 7 / Windows 8 (32-bit/64-bit);
Dimensions (WXDXH) Display screen Weight (with cartridge) Weight (w/o cartridge) Recommended environment Power Noise Power consumption Operating system compatibility	No 6,1 kg(13.4lbs) 5,3 kg(11.7lbs) Recommended temperature: 10-32°C (50-90°F) Recommended humidity: 20% - 80% Model depends on the country of purchase: 110-Volt Model: 100-127VAC,50/60Hz, 6.0A 220-Volt Model: 220-240VAC, 50/60Hz, 3.0A Printing: 54dB; Standby: 35dB Printing: Average 350W; Sleep Mode: Less than 6 W Microsoft Windows Server2003 / Server2008 / Server2012 XP / Vista / Windows 7 / Windows 8 (32-bit/64-bit); Mac OS X 10.4 / 10.5 / 10.6 / 10.7 / 10.8

Consumables*

Standard capacity: 1,500 pages (model depends on the country or region of purchase: PA-110/PB-110/PC-110) High capacity: 2,300 pages (model depends on the country or region of purchase: PA-110H/PB-110H/PC-110H)

What's in the box

Printer X1; 700 page Toner Cartridge X1 USB Interface Cable X1; Power Cord X1 CD-ROM X1; Quick Setup Guide X1

Average yield per toner cartridge in accordance with ISO/IEC 19752 (Individual users will experience di erent results based on their environment and page coverage)

© Copyright 2013 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.



